

County Surveyor's Record, Douglas County, Oregon

14886

Dependent Resurvey of a Portion of the W. Bdy.,
T. 30 S., R. 7 W., Willamette Meridian, Oregon.

CHAINS

A fir, 18 ins. diam., bears N. 38° E., 52 lks. dist., with illegible scribe marks visible on opened blaze.

A rotted madrone stump, size indeterminate, bears S. 56° E., 74 lks. dist., no marks visible.

A fir, 11 ins. diam., bears N. 72° W., 15 lks. dist., with healed blaze.

and trees mkd. by Johnstone, in 1961

A fir, 14 ins. diam., bears S. 69° E., 77 lks. dist., with scribe marks T30S R7W BT visible on open blaze.

A fir, 15 ins. diam., bears S. 37 1/2° W., 102 lks. dist., with healed blaze.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top; with brass cap mkd.

T 30 S
R 8 W R 7 W
S 13 | S 18
S 24 | S 19
1972

Reset iron pipe and deposit corner stone alongside the iron post.

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, cedar, oak, madrone, alder, and maple; undergrowth, salal, fern, hazel, manzanita, and poison oak.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

(Reestablishment of the Survey executed by
William H. Byars, Deputy Surveyor, in 1882)

From the 1/4 sec. cor. of secs. 29 and 30, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1964, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

T 30 S
1/4
S 30 | S 29
R 7 W
1964

from which the remaining original bearing tree:

A fir, 30 ins. diam., bears N. 84° E., 68 lks. dist., no marks visible.

and trees mkd. by Byron, in 1964

A sugar pine, 25 ins. diam., bears S. 18° E.,