

County Surveyor's Record, Douglas County, Oregon

14888 Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 20, 21, 28, and 29, perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1965, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 8 ins. above the ground, with brass cap mkd.

T 30 S
S 20 | S 21
S 29 | S 28
 R 7 W
 1965

from which the remains of the original bearing trees:

A madrone, 18 ins. diam., bears S. 44° E.,
58 lks. dist., with healed blaze, (Record,
S. 42° E.)

A sawed cedar stump, 22 ins. diam., bears S.
40° W., 50 lks. dist., with scribe marks
29 visible on opened blaze.

A fir, 38 ins. diam., bears N. 69° W., 34
lks. dist., with scribe marks T30S R7 S20
visible on bark blaze.

and trees mkd. by Tracy, in 1965

A fir, 8 ins. diam., bears N. 23° E., 9 lks.
dist., with scribe mark S visible on par-
tially healed blaze.

A fir, 22 ins. diam., bears S. 3° E., 18 lks.
dist., with healed blaze.

A fir 22 ins. diam., bears S 81° W., 41 lks.
dist., with healed blaze.

A fir, 11 ins. diam., bears N. 45° W., 64 lks.
dist., with healed blaze.

S. 88° 06'W. bet. secs. 20 and 29.

Descend 15 ft. over SW. slope through heavy timber and moderate undergrowth.

- 0.30 Ravine, drains. SE.; asc. 293 ft. over a broken SE. slope.
 - 14.45 Spur, slopes S. 30° E.; desc. 10 ft. over a SW. slope.
 - 16.10 Ravine, drains. S. 35° E.; desc. 414 ft. over E. slope.
 - 31.50 Spur ridge, slopes N. 15° W.; desc. 115 ft. over NW. slope.
 - 38.76 Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 7 W
 1/4 S 20
S 29
 1972