

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

14889

CHAINS

from which new bearing trees:

A fir, 10 ins. diam., bears N. 73° E., 38 lks.
dist., mkd. 1/4 S20 BT.

A fir, 12 ins. diam., bears S. 18° W., 27 lks.
dist., mkd. 1/4 S29 BT.

Descend 227 ft. over NW. slope.

53.40 Ravine, drains. N. 40° W.; asc. 13 ft. over NE. slope.

54.45 Spur, slopes N. 40° W.; desc. 569 ft. over NW. slope.

55.90 Edge of timber bears N. and S.; enter scattering timber and dense undergrowth.

58.40 Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.

74.50 Ravine, drains. N. 10° E.; asc. 116 ft. over NE. slope.

77.52 The cor. of secs. 19, 20, 29, and 30.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, pine, madrone, and chinquapin;
undergrowth, salal, fern, poison oak, manzanita, and wild rose.

S. 84° 06' W. bet. secs. 19 and 30.

Ascend 239 ft. over NE. slope through scattering timber and dense undergrowth.

3.05 Dirt road, 20 lks. wide, bears N. 20° W. and S. 20° E., curving to SW.

13.80 Spur, slopes N.; desc. 187 ft. over NW. slope.

20.15 Dirt road, 20 lks. wide, bears N. 25° E. and S. 25° W.

27.15 Ravine, drains. N. 35° W.; asc. 134 ft. over NE. slope.

30.80 Spur, slopes N. 10° E., desc. 25 ft. over NW. slope.

32.40 Creek, 2 lks. wide, course N. 50° E.; asc. 147 ft. over NE. slope.

39.00 The 1/4 sec. cor. of secs. 19 and 30, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1964, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 12 ins. above the ground, with brass cap mkd.

T 30 S
1/4 $\frac{S 19}{S 30}$
R 7 W
1964

from which the remains of the original bearing trees:

A root hole, bears N. 5° E., 18 lks. dist.,
alongside of which a fallen fir, size indeterminate, no marks visible.

A fir snag, 40 ins. diam., bears S. 18° E.,
54 lks. dist., with scribe marks 1/4 S visi-