

# County Surveyor's Record, Douglas County, Oregon

14890

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

ble on bark blaze.

and a bearing object mkd. by Byron in 1964

A stone, 5 x 4 x 3 ft., bears S. 14° W.,  
20 1/2 lks. dist., mkd. X on top and B0 on  
S. face.

from which new bearing trees:

A fir, 5 ins. diam., bears S. 15 1/4° W., 37 lks.  
dist., mkd. X BT.

A fir, 6 ins. diam., bears N. 11° W., 49 lks.  
dist., mkd. 1/4 S19 BT.

N. 87° 40' W., beginning new measurement.

Ascend 335 ft. over NE. slope, through scattering timber and dense  
undgergrowth.

- 2.90 Dirt road, 20 lks wide, bears S. 25° E. and N. 55° W. (Question  
this bearing)
- 8.75 Same dirt road, bears N. 15° E. and S. 05° W. (Question this  
bearing)
- 10.95 Rock bluff, 10 ft. high, bears NE. and SW.; asc. 210 ft. over NE.  
slope.
- 18.40 Rock bluff, 40 ft. high, bears N. and S.; asc. 10 ft. over NE.  
slope.
- 19.02 Point for the W 1/16 sec. cor. of secs. 19 and 30.  
  
Set an iron post 28 ins. long, 2 1/2 ins. diam., 24 ins. in the  
ground, with brass cap mkd.  
  

W 1/16    S 19  
           S 30  
           1972
- from which  
  

A fir, 13 ins. diam., bears S. 13 1/4° W., 15 lks.  
dist., mkd. W 1/16 S30 BT.  
  
 A fir, 18 ins. diam., bears N. 62° W., 21 1/2 lks.  
dist., mkd. W 1/16 S 19 BT.
- Ascend 45 ft. over NE. slope.
- 26.05 Spur, slopes N. 40° E.; desc. 24 ft. over NW. slope.
- 35.75 Bottom of descent, drains, N. 10° E.;asc. 32 ft. over NE. slope.
- 40.75 Rock bluff, 10 ft. high, bears N. and S., asc. 25 ft. over NE.  
slope.
- 42.84 The cor. of secs. 19, 24, 25, and 30.

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, hemlock, cedar, pine, live oak, madrone, chinquapin;  
undergrowth, fern, wild rose, manzanita, hazel, huckleberry, and  
salal.

From the cor. of secs. 19, 20, 29, and 30.