

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

14891

CHAINS

N. 0° 05' W. bet. secs. 19 and 20.

Descend 233 ft. over NE. slope through scattering timber and dense undergrowth.

- 6.10 Ravine, drains. N.; desc. 8 ft. along bottom of ravine.
- 8.35 Leave ravine, course N. 20° W.; asc. 59 ft. over SW. slope.
- 18.95 Spur, slopes N. 50° W.; desc. 377 ft. over NW. slope.
- 35.90 Dirt road, 30 lks. wide, bears NE. and SW.
- 39.07 The 1/4 sec. cor. of secs. 19 and 20, perpetuated and recorded by R. H. Gee, Registered Professional Engineer No. 3723, in 1955, for Roseburg Lumber Co.

from which the remains of the original bearing trees:

A root hole, bears S. 87° E., 24 lks. dist., with a fallen cedar, 14 ins. diam., alongside, with axe marks visible on opened blaze.

A cedar, 14 ins. diam., bears S. 85° W., 34 lks. dist., with axe marks visible on opened blaze.

and trees mkd. by Gee, in 1955

A hemlock, 24 ins. diam., bears N. 10 1/2° E., 12 lks. dist., with scribe marks 1/4 S20 T30S R7W BT visible on open double blaze.

A cedar, 12 ins. diam., bears N. 83° W., 84 lks. dist., with scribe marks 1/4 S19 T30S R7W BT visible on open double blaze.

The corner point is located in Wildcat Creek, 10 lks. wide,; course N. 20° W., from S. 20° W., in curve.

From the corner point , a witness corner, set by James W. Byron, Deputy County Surveyor, in 1964, bears East, 7 1/2 lks. dist., monumented with an iron post, 1 in. diam., firmly set, protruding 14 ins. above the ground, and in a mound of stone, 1 1/2 ft. base, 1 ft. high, with brass cap mkd.

T 30 S		
WIT		COR
5 F		TW
1/4		TO
S 19		S20
		R 7 W
		1964

from which a tree mkd. by Byron, in 1964

A hemlock, 16 ins. diam., bears S. 5° W., 99 lks. dist., with illegible scribe marks visible on partially healed double blaze.

N. 0° 06' W., beginning new measurement.

Ascend 3 ft. over SW. slope through scattering timber and dense undergrowth.