

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

14893

CHAINS

From the cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by Vernon Tracy, Dputy County Surveyor, in 1965, monumented with an iron post, 1 in. diam., protruding 8 ins. above the ground, with brass cap mkd.

T 30 S
S 17 | S 16
S 20 | S 21
 R 7 W
 1965

from which the remaining original bearing tree:

A fir, 38 ins. diam., bears N. 10° W., 45 lks. dist. with scribe marks T30S R7W visible on bark blaze.

and trees mkd. by Tracy, in 1965

A fir, 13 ins. diam., bears N. 64° E., 16 1/2 lks. dist., with illegible scribe marks visible on open blaze.

A fir, 14 ins. diam., bears S. 37° E., 14 lks. dist., with illegible scribe marks visible on open blaze.

A fir, 14 ins. diam., bears S. 81° W., 40 lks. dist., with partially healed blaze.

A fir, 9 ins. diam., bears N. 39° W., 46 lks. dist., with healed blaze.

S. 88° 49' W. bet. secs. 17 and 20.

Ascend 173 ft. over NE. slope through moderate timber and dense undergrowth.

- 5.25 Ridge, divides Cow Creek drainage and Wildcat Creek drainage, bears N. 20° E. and S. 20° W.; desc. 621 ft. over NW. slope.
- 31.75 Ravine drains S. 55°W.; asc. 75 ft. over SE. slope.
- 36.15 Spur, slopes N. 20P W.; desc. 35 ft. over SW. slope.
- 38.68 Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 7 W
 1/4 S 17
S 20
 1972

from which new bearing trees

A fir, 7 ins. diam., bears N. 65 1/2° W., 104 lks. dist., mkd. 1/4 S17 BT.

A fir, 34 ins. diam., bears S. 29° E., 46 lks. dist., mkd. 1/4 S20 BT. this tree previously mkd. by person(s) unknown with scribe marks 1/4S BT visible on bark blaze.

Descend 171 ft. over SW. slope.