

County Surveyor's Record, Douglas County, Oregon

11894

Dependent Resurvey of a Poriton of the Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon.

CHAINS	
42.10	Dirt Road, 20 lks. wide, bears N. 30° E and S. 30° W.
46.00	Creek, 2 lks. wide, course N. 45° W.; asc. 263 ft. over NE. slope.
51.25	Dirt road, 20 lks. wide, bears N. 45° W. and S. 30° E.
56.90	Dirt road, 20 lks. wide, bears. N. 30° W.; and S. 30° E.; also slope changes to SE.
57.95	Spur, slopes S. 10° W.; desc. 263 ft. over NW. slope.
60.85	Sirt road, 20 lks. wide, bears N. 10° E. and S. 10° E.; curving to E.
77.10	East edge of dirt road, 30 lks. wide, bears North and S. 10°W.
77.36	The cor. of secs. 17, 18, 19, and 20.
	Land, mountainous. Soil, rocky clay Timber, fir, cedar, pine, madrone, chinquapin, hemlock, and live oak: undergrowth, fern manzanita, salal, huckleberry, and hazel.
	S. 88° 07' W. bet. secs. 18 and 19.
	Descend 44 ft. across road and over NW. slope through moderate timber and dense undergrowth.
0.05	West edge of gravelled road, bears North and S. 10° W.
1.25	Dirt road, 15 lks. wide, bears N. 35° E. and S. 35° W.
2.90	Wildcat Creek, 10 lks. wide, course N. 30° E.; ascend 620 ft. over E. slope.
16.05	Rock bluff, 20 ft. high, bears. N. and S.; continue ascent.
18.30	Spur, slopes N. 35° E.; desc. 10 ft. over NW. slope.
19.27	Point for the E 1/16 sec. cor. of secs. 18 and 19.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	$E \frac{1}{16} \begin{matrix} S 18 \\ S 19 \end{matrix}$ 1972
	from which
	A fir, 7 ins. diam., bears N. 61° E., 12 1/2 lks. dist., mkd. E 1/16 S18 BT.
	A fir, 10 ins. diam., bears S. 45° W.; 37 lks. dist., mkd. E 1/16 S19 BT
	Descend 50 ft. over NW. slope.
35.55	Ravine, drains. N. 30° E.; asc. 72 ft. over NE. slope.
38.54	The original 1/4 sec. cor. of secs. 18 and 19, determined at record bearing and distance from the remains of the original bearing trees: