

County Surveyor's Record, Douglas County, Oregon

14895

Dependent Resurvey of a Portion of the subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 10° E., 46 lks. dist., with the rotted remains of a fir alongside, size indeterminate. No marks remaining.

A cedar snag, 45 ins. diam., bears S. 19° E., 45 lks. dist., with scribe mark 4 visible on opened blaze.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 7 W
1/4 S 18
S 19
1972

from which new bearing trees

A fir, 15 ins. diam., bears N. 51° W., 23 1/4 lks. dist., mkd. 1/4 S18 BT.

A fir, 7 ins. diam., bears S. 17° W., 41 lks. dist., mkd. 1/4 S19 BT.

S. 88° 17' W., beginning new measurement.

Ascend 86 ft. over NE. slope.

6.60 Spur, slopes N. 15° E.; desc. 39 ft. over NW. slope.

10.35 Ravine, drains N. 20° E.; asc. 130 ft. over E. slope.

17.90 Spur, slopes N. 30° E.; desc. 14 ft. over NW. slope.

19.16 Point for the W 1/16 sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S 18}{S 19}$
1972

from which

A fir, 9 ins. diam., bears N. 35° E., 13 lks. dist., mkd. W 1/16 S18 BT.

A fir, 9 ins. diam., bears S. 23 1/2° E., 73 lks. dist., mkd. W 1/16 S19 BT.

Descend 581 ft. over NW. slope.

31.90 Dirt road, 20 lks. wide, bears N. 40° E. and S. 30° W., curving to E.

34.50 Ravine, drains N. 35° W.; asc. 38 ft. over NE. slope.

37.75 Spru, slopes N. 50° W.; desc. 115 ft. over NW. slope.

43.24 The cor. of secs. 13, 18, 19, and 24.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, pine, cedar, alder, maple, live oak, chinquapin, and madrone; undergrowth, poison oak, fern, salal, rhododendron, hazel, manzanita, and huckleberry.