

County Surveyor's Record, Douglas County, Oregon

34896

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	From the cor. of secs. 17, 18, 19, and 20.
	N. 1° 00' E. bet. secs. 17 and 18.
	Descend 57 ft. over NW. slope through scattering timber and dense undergrowth, along gravelled road.
8.75	Bottom of descent, drains. W.; ascend 39 ft. over SW. slope. Also leave gravelled road, bears NW. and S.
16.60	Top of ascent slopes W.; descnded 21 ft. over NW. slope.
19.83	Point for the S 1/16 sec. cor. of secs. 17 and 18.
	Set on iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mdk.
	S 1/16 S 18/S 17 1972
	from which
	A fir, 23 ins. diam., bears S. 54 3/4° E., 99 lks. dist., mkd. S 1/16 S17 BT.
	A fir, 3 ins. diam., bears N. 49° W., 45 1/2 lks. dist., mkd. X BT on bark blaze.
	Descend 73 ft. over NW. slope.
20.50	Dirt road, 15 lks. wide, bears N. 85° W. and S. 75° E.
21.80	Creek, 2 lks. wide, course W.; asc. 25 ft. over SW. slope.
23.00	Top of ascent, slopes W.; desc. 13 ft. over NW. slope.
23.80	Creek, 1 lk. wide, course S. 70° W.; asc. 351 ft. over SW. slope.
24.15	Dirt road, 20 lks. wide, bears N. 85° W. and S. 60° E.
39.10	Spur, slopes N. 40° W.; desc. 7 ft. over NW. slope.
39.66	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance. There is no remaining evidence of the original corner.
	Set an iron psot 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 30 S R 7 W 1/4 S 18/ S 17 1972
	from which new bearing trees
	A chinquapin, 8 ins. diam., bears N. 84° E., 58 1/2 lks. dist., mkd. 1/4 S17 BT.
	A fir, 6 ins. diam., bears S. 61° W., 16 1/2 lks. dist., mkd. 1/4 S18 BT.
	Descend 300 ft. over broken NW. slope.
42.10	Dirt road, 15 lks. wide, bears S. 10° E. and N. 25° W. to N.