

County Surveyor's Record, Douglas County, Oregon 14901

Dependent Resurvey, Poriton of Subdivisional Lines, T. 22 S., R. 9 W.,

CHAINS

with an iron bar, 1/2 in. diam., firmly set, projecting 6 ins. above ground, from which the remaining original bearing tree:

A fir stump, 54 ins. diam., bears S. 30° W.,
45 lks. dist., with partial scribe marks
visible on open blaze.

and bearing trees mkd. by the County Surveyor, in 1961

A maple, 18 ins. diam., bears N. 57° E.,
37 lks. dist., with partial scribe marks
visible on open blaze.

An alder, 15 ins. diam., bears S. 33° E.,
88 1/2 lks. dist., with partial scribe marks
visible on open blaze.

An alder, 13 ins. diam., bears S. 58 ° W.,
26 lks. dist., with partial scribe marks
visible on open blaze.

A fir, 15 ins. diam., bears N. 77 1/2° W.,
65 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 22 S R 9 W
S 18 | S 17
S 19 | S 20
1970

Deposit the iron bar alongside the iron post.

N. 0° 01' E., bet. secs. 17 and 18 marking and blazing the true line.

Descend 110 ft. over broken NW. slope. through scattering timber and dense undergrowth.

- 5.15 Ravine, drains. W.; asc. 130 ft. over broken SW. slope.
- 9.80 Ridge, bears N. 20° W. and S. 20° E.; desc. 180 ft. over broken NE. slope.
- 14.10 Ravine, drains. N. 25° W.; asc. 90 ft. over SW. slope.
- 19.35 Spur, slopes W.; desc. 15 ft. over NW. slope.
- 20.15 Point for the S 1/16 sec. cor. of secs. 17 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 18 | S 17
1970

from which

A fir, 15 ins. diam., bears N. 61 1/2° E.,
29 lks. dist., mkd. S 1/16 S17 BT.

A fir, 10 ins. diam., bears S. 44° W.,
17 lks. dist., mkd. S 1/16 S18 BT.