

County Surveyor's Record, Douglas County, Oregon

1906

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon.

CHAINS

N. 0° 25' E., bet. secs. 7 and 8.

Ascend 140 ft. over SW. slope. through scattering timber and scattering undergrowth.

7.25 Gravelled road, 20 lks. wide, bears N. 45° W. and S. 45° E.

11.40 Top of ascent, slopes W.; desc. 25 ft. over NW. slope.

21.85 Bottom of descent, slopes W.; asc. 55 ft. over S. slope.

23.55 Same gravelled road, 20 lks. wide, bears N. 70° E. and S. 70° W.

24.95 Gravelled road, 10 lks. wide, bears N. 70° W. and S. 70° E.

28.80 Spur, slopes W.; desc. 230 ft. over N. slope.

33.80 Left bank of the Umpqua River, course W.; thence across river.

41.50 Right bank of the Umpqua River, asc. 108 ft. over S. slope.

44.30 Spur, slopes E.; desc. 35 ft. over N. slope.

51.27 Intersect the N. bdy. of Donation Land Claim No. 38, and point for the closing sec. cor. of secs. 7 and 8.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, mkd. X, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

C C
T 22 S | R 9 W
S 7 | S 8
C 38
1970

from which a bearing object and a bearing tree established by persons unknown

A sandstone outcrop, 5 x 3 x 2 ft. above ground, bears N. 44° W., 23 1/2 lks. dist., mkd. with an X on top.

A fir, 42 ins. diam., bears N. 53° W., 50 lks. dist., with partial scribe marks visible on open blaze.

and a new bearing tree

An alder, 10 ins. diam., bears N. 75 1/2° E., 63 1/2 lks. dist., mkd. T22S R9W S8 CC BT.

Deposit broken brown glass at the base of the iron post.

From this point, the witness cor. for the NE. cor. of Donation Land Claim No. 38, bears N. 89° 05' E., 14.97 chs. dist., determined from original calls of the record:

A sandstone bluff, 20 ft. long, 20 ft. high, faces S., bears North, 4 1/2 lks. dist.