

County Surveyor's Record, Douglas County, Oregon

14914

Dependent Resurvey, Portion of W. Bdy.,
T. 30 S., R.2 W., Willamette Meridian, Oregon

CHAINS

quartz stone, 16 x 12 x 12 ins., firmly set, protruding 4 ins. above ground, marked with 1 groove on N., and 5 grooves on S. face, alongside of which is an iron post, 1 1/2 ins. diam., firmly set, protruding 16 ins. above ground, set and recorded by the Douglas County Surveyor, in 1963, with brass cap marked

COUNTY SURVEYORS OFFICE
R T 30 S R
3 S 1 S 6 2
W S 12 S 7 W
1963

from which the original bearing trees

A fir, 35 ins. diam., bears N. 44° E.,
97 lks. dist., with healed blaze.

A fir, 30 ins. diam., bears S. 45° E.,
20 lks. dist., with healed blaze.

A fir, 23 ins. diam., bears S. 33° W.,
60 lks. dist., with scribe marks T30N
R3W S12 BT visible on opened blaze.

A root hole, bears N. 67 1/2° W., 19 1/2 lks. dist.,
with a down fir, 39 ins. diam., alongside,
with healed blaze.

and bearing trees marked by the County Surveyor

A chinquapin, 12 ins. diam., bears N. 32° E.,
6 lks. dist., with scribe marks T30S R3W
S6 CS BT visible on open double blaze.

A hemlock, 11 ins. diam., bears N. 4 3/4° W.,
22 lks. dist., with scribe marks T30N R3W
S1 CS BT visible on open double blaze.

N. 0° 05' W., along the W. bdy. of sec. 6, marking and blazing
the true line.

Descend 290 ft. over NE. slope, through heavy timber and light
undergrowth.

15.20 Creek, 20 lks. wide, course S. 30° E.; asc. 645 ft. along E. slope.

39.20 The 1/4 sec. cor. of sec. 6 only, perpetuated and recorded by
James W. Byron, Deputy County Surveyor, in 1962, monumented by
a fir, 40 ins. diam., with healed blaze on W. face, from which
the original bearing trees:

A fir, 42 ins. diam., bears N. 56° E.,
68 lks. dist., with healed blaze.

A fir, 34 ins. diam., bears S. 5° E.,
93 lks. dist., with healed blaze.

and a bearing tree and reference monument by Byron

A fir, 8 ins. diam., bears S. 38° E., 65 lks.
dist., with healed blaze.

An iron post, 1 1/2 ins. diam., firmly set,
protruding 18 ins. above ground, bears East,
3 lks. dist., with brass cap marked.