

County Surveyor's Record, Douglas County, Oregon

4915

Dependent Resurvey, Portion of W. Bdy.,
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 30 S
R 1/4 R
3 S 6 2
W W
WEST
1962

N. 0° 05' W., beginning new measurement.

Ascend 15 ft. along E. slope.

1.09 The 1/4 sec. cor. of sec. 1 only, determined at record bearing and distance from the original bearing trees

A fir, 30 ins. diam., bears S. 86° E.,
52 1/4 lks. dist., with healed blaze.
(Record bearing N. 89° E.) Mensch reported
destroying the marks on this tree in 1908.

A fir, 40 ins. diam., bears N. 57 1/2° W.,
38 lks. dist., with healed blaze. (Mensch
record)

and a bearing tree marked by Mensch in 1908


A madrone, 32 ins. diam., bears S. 41° W.,
10 lks. dist., with no marks remaining on
opened and rotted blaze.

and a bearing tree marked by the County Surveyor in 1962

A fir, 10 ins. diam., bears S. 44 1/2° W.,
24 1/2 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked




N. 0° 23' W., beginning new measurement.

Ascend 60 ft. over SE. slope.

4.00 Top of ascent, slopes E.; desc. 65 ft. over NE. slope.

9.67 The NE. cor. of T. 30 S., R. 3 W., perpetuated and recorded by James W. Byron, County Surveyor, in 1962, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 14 ins. above ground, with brass cap marked



from which the original bearing trees