

County Surveyor's Record, Douglas County, Oregon

14917

Dependent Resurvey, Portion of N. Bdy.,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

destroying marks on this tree.

A fir, 20 ins. diam., bears N. 45° W.,
4lks. dist., with healed blaze. (Bushey
record)

and a new reference monument

An iron post, 28 ins. long, 2 1/2 ins. diam.,
set 22 ins. in the ground, for a reference
monument, bears N. 56° W., 30 lks. dist.,
with brass cap marked T29S R3W S36 RM 1971
and an arrow pointing to the corner.

Dependent Resurvey of a Portion of the E. Bdy.,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the 1881 survey by William H. Byars,
and the 1908 resurvey by Fred Mensch)

From the SE. cor. of T. 29 S., R. 3 W.

N. 0° 23' W., along the E. bdy. of sec. 36.

Ascend 50 ft. over SE. slope, through scattering timber and light
undergrowth.

4.50 Top of ascent, slopes E.; desc. 230 ft. over NE. slope.

12.85 Ravine, drains. E.; asc. 155 ft. over SE. slope.

25.45 Top of ascent, slopes SE.; desc. 55 ft. over NE. slope.

27.20 Ravine, drains. E.; asc. 50 ft. over S. slope.

27.70 Spur, slopes E.; desc. 70 ft. over NE. slope.

32.87 The original closing cor. of Tps. 29 and 30 S., R. 2 W.; here-
in after described.

39.00 The 1/4 sec. cor. of sec. 36 only, remonumented by Mensch in 1908,
with a slate stone, 18 x 15 x 10 ins., firmly set, 10 ins. in the
ground, marked 1/4 on W. face, from which the bearing trees marked
by Mensch

A fir, 42 ins. diam., bears S. 15° W.,
18 lks. dist., with healed blaze.

A madrone, stump, 30 ins. diam., bears
N. 59° W., 70 lks. dist., with healed
blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the
ground, with brass cap marked

1/4	
S 36	
T 29 S	
R 3 W	
1971	

from which a new bearing tree