

# County Surveyor's Record, Douglas County, Oregon

14918

Dependent Resurvey, Portion of E. Bdy.,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A fir, 8 ins. diam., bears N. 35° W.,  
79 lks. dist., marked 1/4 S36 BT.

Deposit corner stone alongside the iron post.


Land, mountainous.  
Soil, rocky clay.  
Timber, fir, cedar, pine, madrone, hemlock, chinquapin, alder, maple, and dogwood; undergrowth, poison oak, manzanita, fern, blackberry, vine maple, hazel, willow, Oregon grape, salal, huckleberry, arrowwood, and wild rose.

Dependent Resurvey of a Portion of the N. Bdy.,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the 1908 survey by Fred Mensch,  
and the 1917 resurvey by Elmer F. Strickler)

From the cor. of secs. 5 and 6 only, on the N. bdy. of the township, perpetuated and recorded by the County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE



from which the original bearing trees

A fir, 43 ins. diam., bears N. 50° E.,  
75 lks. dist., with healed blaze. (Strickler reported destroying the marks on this tree in 1917)

A fir, 25 ins. diam., bears S. 27° E.,  
18 lks. dist., with healed blaze.

A fir, 38 ins. diam., bears S. 16° W.,  
46 lks. dist., with healed blaze.

A fir, 53 ins. diam., bears N. 65° W.,  
16 lks. dist., with healed blaze. (Strickler reported destroying the marks on this tree in 1917)

and a bearing tree marked by the County Surveyor in 1968

A cedar, 10 ins. diam., bears N. 34 ° E.,  
25 lks. dist., with scribe marks T29S R2W  
S32 CS BT visible on open blaze.

S. 89° 54' W., along the N. bdy. of sec. 6.

Ascend 160 ft. over SE. slope, through scattering timber and dense undergrowth.

1.11 Intersect the cor. of secs. 31 and 32, T. 29 S., R. 2 W., only, perpetuated and recorded by the County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly