

County Surveyor's Record, Douglas County, Oregon

14919

Dependent Resurvey, Portion of N. Bdy.,
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

set, protruding 8 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE

	T 29 S		
R		R	
2 S	31	S 32	2
W	S 6	W	
	T 30 S		
	1968		

from which the original bearing trees

A fir, 17 ins. diam., bears N. 6 1/2° E.,
21 lks. dist., with healed blaze.

A fir, 28 ins. diam., bears N. 38 1/4° W.,
54 lks. dist., with no marks visible
on opened blaze.

and a bearing tree marked by the County Surveyor in 1968

A fir, 12 ins. diam., bears S. 2° E.,
28 lks. dist., with no marks visible
on pitched over blaze.

and a new bearing tree

A fir, 13 ins. diam., bears N. 70° W.,
47 lks. dist., marked T29S R2W S31
BT.

13.90 Top of ascent, slopes S.; desc. 85 ft. over SW. slope.

16.70 Ravine, drains. S. ; asc. 70 ft. over SE. slope.

19.88 Point for the E 1/16 sec. cor. of sec. 6 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap marked

E 1/16 S 6
1971

from which

A fir, 10 ins. diam., bears S. 57° E.,
52 lks. dist., marked E 1/16 S6 BT.

A madrone, 8 ins. diam., bears S. 53° W.,
28 lks. dist., marked E 1/16 S6 BT.

Ascend 90 ft. over SE. slope.

31.55 Spur, slopes S.; desc. 35 ft. over SW. slope.

34.15 Head of ravine, drains. S.; asc. 145 ft. over SE.

39.76 The 1/4 sec. cor. of sec. 6 only, perpetuated and recorded by the County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap marked.