

County Surveyor's Record, Douglas County, Oregon

1920

Dependent Resurvey, Portion of N. Bdy.,
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 29 S
 R 2 W 1/4
 S 6
T 30 S
1968

alongside of which, the original porphyry stone, 14 x 12 x 6 ins., loosely set, 2 ins. in the ground, marked 1/4 on N. face, from which the original bearing trees

A fir, 15 ins. diam., bears N. 35° E.,
4 lks. dist., with healed blaze. (Record bearing, N. 35° W.) Strickler reported destroying the marks on this tree in 1917.

A madrone, 9 ins. diam., bears S. 40° E.,
3 1/2 lks. dist., with no marks visible on open healed double blaze.

and a bearing tree marked by Strickler in 1917

A rotted fir stump, size indeterminate, bears S. 2 1/4° E., 20 lks. dist., with axe marks visible.

and bearing trees marked by the County Surveyor in 1968

A fir, 7 ins. diam., bears S. 43 1/2° E.,
27 lks. dist., with scribe marks 1/4 S6
CS BT visible on open blaze.

A fir, 30 ins. diam., bears S. 35° W.,
29 lks. dist., with healed blaze.

S. 89° 53' W., beginning new measurement.

Ascend 65 ft. over SE. slope. through scattering timber and light undergrowth.

1.35 From this point, the 1/4 sec. cor. of sec. 31 only, bears North, 0.025 chs. dist., monumented with an iron post, 1 in. diam., firmly set, protruding 10 ins. above ground, with brass cap marked

1/4 S 31
1917

from which the original bearing trees

A root hole, bears N. 8 1/2° E., 19 lks. dist., with a down fir, 25 ins. diam., alongside, with no marks visible.

A fir, 40 ins. diam., bears N. 32 1/2° W.,
30 lks. dist., with healed blaze.

and a bearing tree marked by the County Surveyor in 1968

A fir, 23 ins. diam., bears N. 30° E.,
38 lks. dist., with scribe marks 1/4 S31
CS BT visible on open blaze.

3.45 Spur, slopes SW.; desc. 995 ft. over W. slope.

28.50 Coffee Creek, 6 lks. wide, course S.; asc. 435 ft. over E. slope.