

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Poriton of N. Bdy.,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon

14921

**CHAINS**

- 39.45 Top of ascent, slopes SE.; desc. 40 ft. over SW. slope.
- 46.05 Creek, 1 lk. wide, course SE. ; asc. 15 ft. over E. slope.
- 46.44 Intersect the E. bdy. of T. 29 S., R. 3 W.

The closing cor. of Tps. 29 and 30 S., R. 2 W., monumented with an iron post, 3 ins. diam., firmly set, protruding 12 ins. above ground, with brass cap marked

	T 29 S	
T 29 S	R 2 W	
S 36	S 31	CC
R 3 W	S 6	
	T 30 S	
	1917	

from which the original bearing trees

A hemlock, 18 ins. diam., bears N. 44° E.,  
22 lks. dist., with scribe marks R W 31  
T visible on partially healed blaze.

A hemlock, 20 ins. diam., bears S. 40 1/2° E.,  
48 lks. dist., with scribe mark 6 visible  
on partially healed blaze.

From this point, the 1/4 sec. cor. of sec. 36 only, T. 29 S., R. 3 W., bears N. 0° 23' W., 6.13 chs. dist., hereinfore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, pine, madrone, hemlock, chinquapin, alder, maple, and dogwood; undergrowth, poison oak, manzanita, fern, blackberry, vine maple, hazel, willow, Oregon grape, salal, huckleberry, arrowwood, and wild rose.

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon

(Restoring the 1909 survey by Fred Mensch)

From the cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above ground, with brass cap marked

T 30 S	R 2 W
S 6	S 5
S 7	S 8
1970	

alongside of which, an iron pipe, 1 1/4 ins. diam., firmly set, protruding 6 ins. above the ground, from which the original bearing trees

A madrone, 21 ins. diam., bears N. 75 1/2° E.,  
24 lks. dist., with scribe marks T30S  
R2W S5 visible on open blaze.

A fir, 33 ins. diam., bears S. 43 1/2° E.,  
42 lks. dist., with scribe marks S8 BT  
visible on bark blaze.