

County Surveyor's Record, Douglas County, Oregon

1922

Dependent Resurvey, Portion of Subdivisional Lines
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

A madrone, 12 ins. diam., bears S. 23 1/2° W.,
37 lks. dist., with no marks remaining
on rotted blaze.

A madrone, 20 ins. diam., bears N. 70° W.,
28 lks. dist., with scribe marks S6 BT
visible on bark blaze.

and bearing trees marked by the County Surveyor in 1963

A fir, 6 ins. diam., bears S. 15° W.,
11 lks. dist., with scribe marks CS S7
BT visible on open double blaze.

A madrone, 12 ins. diam., bears N. 1° W.,
28 lks. dist., with scribe marks T30S
R2W S5 CS BT visible on open blaze.

N. 0° 20' E., bet. secs. 5 and 6.

Ascend 80 ft. over SE. slope. through scattering timber and light
undergrowth.

7.35 Spur, slopes W.; desc. 140 ft. over NW. slope.

14.30 Creek, 2 lks. wide, course W.; asc. 485 ft. over SE. slope.

39.82 The 1/4 sec. cor. of secs. 5 and 6, monumented with a slate stone,
14 x 8 x 6 ins., firmly set, 8 ins. in the ground, with no marks
visible, from which the original bearing trees

A madrone, 19 ins. diam., bears S. 10° E.,
27 lks. dist., with no marks visible on
opened and rotted blaze.

A cedar, 31 ins. diam., bears S. 32° W.,
65 lks. dist., with healed blaze. (Record,
S. 35° W., 69 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the
ground, with brass cap marked

1/4
S 6 | S 5
T 30 S | R 2 W
1971

from which a new bearing tree

A fir, 30 ins. diam., bears N. 35° E.,
16 lks. dist., marked 1/4 S5 BT.

Deposit corner stone alongside the iron post.

N. 0° 05' W., beginning new measurement.

Ascend 130 ft. over SE. slope, through scattering timber and light
undergrowth.

8.65 Spur, slopes E.; desc. 360 ft. over NW. slope.

19.64 Point for the N 1/16 sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.