

County Surveyor's Record, Douglas County, Oregon

14923

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

in the ground, with brass cap marked

N 1/16
S 6 | S 5
1971

from which

A hemlock, 8 ins. diam., bears S. 69° E.,
12 1/2 lks. dist., marked N 1/16 S5 BT.

A hemlock, 8 ins. diam., bears N. 6 1/2° W.,
7 lks. dist., marked N 1/16 S6 BT.

Descend 285 ft. over NW. slope.

29.40 Texas Gulch Creek, 2 lks. wide, course W.; asc. 310 ft. over SE. slope.

30.00 Texas Gulch Road, 20 lks. wide, bears E. and W.

42.81 The cor. of secs. 5 and 6 only, on the N. bdy. of the Tp.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, pine, madrone, hemlock, chinquapin, alder, maple, and dogwood; undergrowth, poison oak, manzanita, fern, blackberry, vine maple, hazel, willow, Oregon grape, salal, huckleberry, arrowwood, and wild rose.

Subdivision of Section 6, T. 30 S., R. 2 W.,
Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

T 30 S R 2 W
1/4 $\frac{S 6}{S 7}$
1970

with the original corner stone and an iron pipe alongside, from which an original bearing tree

A pine, 37 ins. diam., bears N. 80 1/2° E.,
65 lks. dist., with healed blaze.

and trees mkd. by the County Surveyor in 1967

A fir, 25 ins. diam., bears S. 89 1/2° W.,
136 lks. dist., with scribe marks 1/4 S7
CS BT visible on open blaze.

A twin madrone, 19 ins. diam., bears N. 1° W.,
48 lks. dist., with scribe marks 1/4 S6 CS
BT visible on open blaze.

N. 0° 08' E., on the N. and S. center line of sec. 6.

Ascend 125 ft. over SW. slope, through scattering timber and light undergrowth.

7.95 Spur, slopes NW.; desc. 505 ft. over NE. slope.