

# County Surveyor's Record, Douglas County, Oregon

1924

Subdivision of Section 6

T. 30 S., R. 2 W., Willamette Meridian, Oregon

**CHAINS**

8.50 Dirt road, 20 lks. wide, bears S. 35° W. and N. 35° E.  
 31.35 Creek, 2 lks. wide, course NW.; asc. 30 ft. along W. slope.  
 34.30 Top of ascent, slopes NW.; desc. 75 ft. over N. slope.  
 39.71 Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line of sec. 6.  
 Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap marked.

C 1/4 S 6  
 T 30 S R 2 W  
 1971

from which

A fir, 15 ins. diam., bears N. 5° E.,  
 115 lks. dist., marked C1/4 S6 BT.

An alder, 7 ins. diam., bears S. 60° W.,  
 57 lks. dist., marked C 1/4 S6 BT.

Descend 65 ft. over N. slope.

43.00 Texas Gulch Creek, 2 lks. wide, course SW. ; asc. 405 ft. over SE. slope.  
 43.45 Texas Gulch Road, 20 lks. wide, bears N. 70° E. and S. 70° W.  
 59.51 Point for the center N 1/16 sec. cor. of sec. 6.  
 Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap marked

C  
 |  
 N 1/16 | S 6  
 |  
 C  
 1971

from which

A pine, 10 ins. diam., bears N. 71° E.,  
 68 lks. dist., marked CN 1/16 S6 BT.

A fir, 5 ins. diam., bears S. 56° W.,  
 30 lks. dist., marked CN 1/16 S6 BT.

Ascend 445 ft. over SE. slope.

82.87 The 1/4 sec. cor. of sec. 6 only

From the 1/4 sec. cor. of secs. 5 and 6.  
 S. 89° 21' W., on the E. and W. center line of sec. 6.  
 Ascend 95 ft. over SE. slope. through heavy timber and light undergrowth.

11.60 Dirt road, 20 lks. wide, bears S. 20° W. and N. 20° E.  
 11.80 Ridge, bears NE. and SW.; desc. 225 ft. over W. slope.  
 19.97 Point for the center E 1/16 sec. cor. of sec. 6.