

# County Surveyor's Record, Douglas County, Oregon

14926

Subdivision of Section 6,  
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	over S. slope.
19.72	Point for the NE. 1/16 sec. cor. of sec. 6, at intersection with the E. and W. center line of the NE 1/4 of sec. 6.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked  NE 1/16 S 6 1971  from which  A fir, 14 ins. diam., bears N. 71° E., 64 lks. dist., marked NE 1/16 S6 BT.  A cedar, 13 ins. diam., bears S. 70° W., 61 lks. dist., marked NE 1/16 S6 BT.  Ascend 565 ft. over S. slope.
19.85	Texas Gulch Road, 20 lks. wide, bears S. 60° W. and N. 60° E.
42.92	The E 1/16 sec. cor. of sec. 6 only, on the N. bdy. of the Tp.
<p>From the N 1/16 sec. cor. of secs. 5 and 6.  S. 89° 34' W., on the E. and W. center line of the NE 1/4 of sec. 6.  Ascend 20 ft. along N. slope. through heavy timber and light undergrowth.</p>	
1.45	Spur, slopes NW.; desc. 125 ft. over broken NW. slope.
7.70	Ravine, drains. N.; asc. 20 ft. over NE slope.
9.50	Spur, slopes NW.; desc. 280 ft. over NW. slope.
19.40	Texas Gulch Creek, 4 lks. wide, course SW.; asc. 5 ft. along S. slope.
19.95	The NE 1/16 sec. cor. of sec. 6.  Ascend 305 ft. along S. slope.
20.10	Texas Gulch Road, 20 lks. wide, bears NE. and SW.
38.75	Top of ascent, slopes SW.; desc. 5 ft. along S. slope.
39.89	The center N 1/16 sec. cor. of sec. 6.
<p>From the E 1/16 sec. cor. of secs. 6 and 7, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above ground, with brass cap marked  E 1/16 <math>\frac{S\ 6}{S\ 7}</math> 1970  from which bearing trees marked by Harvey E. Wofford in 1970  A pine, 8 ins. diam., bears N. 23 1/3° E.,</p>	