

County Surveyor's Record, Douglas County, Oregon

14927

Subdivision of Section 6,
T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

15 lks. dist., with scribe marks E 1/16
S6 BT visible on open blaze.

A pine, 54 ins. diam., bears S. 63° E.,
58 lks. dist., with scribe marks E 1/16
S7 BT visible on open blaze.

N. 0° 13' E., on the N. and S. center line of the SE 1/4
of sec. 6.

Ascend 20 ft. over S. slope, through scattering timber and light
undergrowth.

- 1.00 Spur, slopes SE.; desc. 90 ft. over NE. slope.
- 4.90 Creek, 2 lks. wide, course SE.; asc. 360 ft. along E. slope.
- 29.70 Ridge, bears NE. and SW.; desc. 160 ft. along W. slope.
- 29.80 Dirt road, 15 lks. wide, bears NE. and SW.
- 39.82 The center E 1/16 sec. cor. of sec. 6.

From the W 1/16 sec. cor. of secs. 6 and 7, monumented with an
iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above
the ground, with brass cap marked

$$W \frac{1}{16} \frac{S \ 6}{S \ 7}$$

1970

from which bearing trees marked by Harvey E. Wofford in 1970

A hemlock, 15 ins. diam., bears N. 22 1/2° E.,
75 lks. dist., with scribe marks W 1/16
S6 BT visible on open blaze.

A fir, 6 ins. diam., bears S. 0 3/4° W., 72 lks.
dist., with scribe marks W 1/16 S7 BT
visible on open blaze.

N. 0° 11' E., on the N. and S. center line of the SW 1/4
of sec. 6.

Descend 60 ft. along W. slope. through heavy timber and light
undergrowth.

- 3.15 Ravine, drains. W.; asc. 30 ft. along W. slope.
- 6.90 Top of ascent, slopes NW.; desc. 60 ft. over broken NW. slope.
- 32.95 Texas Gulch Road, 20 lks. wide, bears N. 30° E. and S. 30° W.
- 33.95 Texas Gulch Creek, 3 lks. wide, course SW.; asc. 145 ft. over S.
slope.
- 39.48 The center W 1/16 sec. cor. of sec. 6

GENERAL DESCRIPTION

The area covered in the foregoing survey is located ap-
proximately 5 miles northwest of Tiller, Oregon.