

County Surveyor's Record, Douglas County, Oregon

14931

Dependent Resurvey, Portion of subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A fir snag, 14 ins. diam., bears N. 80° E., 10 lks. dist., with fragmentary scribe marks visible on opened blaze.

A fir, 27 ins. diam., bears S. 15° E., 24 lks. dist., with scribe marks BT visible on opened blaze.

and bearing trees marked by Byron

A fir, 15 ins. diam., bears S. 53 1/2° W., 50 lks. dist., with scribe marks T31S R8W S20 CS BT visible on open blaze.

A fir, 32 ins. diam., bears N. 33 1/2° W., 18 lks. dist., with scribe marks T31S R8W visible on partially healed blaze.

and a bearing tree marked by White, Corbin, and Beck

A fir, 24 ins. diam., bears N. 83 1/2° E., 55 lks. dist., with healed blaze.

S. 88° 45' W., bet. secs. 17 and 20, marking and blazing the true line.

Descend 610 ft. over W. slope. through heavy timber and moderate undergrowth.

19.51 Point for the E 1/16 sec. cor. of secs. 17 and 20.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 17}{S\ 20}$
1973

from which

A fir, 8 ins. diam., bears N. 27 1/2° E., 35 lks. dist., mkd. E 1/16 S17 BT.

A fir, 12 ins. diam., bears S. 13° W., 11 lks. dist., mkd. E 1/16 S20 BT.

Descend 335 ft. over NW. slope.

39.02 Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins diam., 22 ins. in the ground, with brass cap mkd.

T 31 S R 8 W
1/4 $\frac{S\ 17}{S\ 20}$
1973

from which

A fir, 20 ins. diam., bears N. 58° W., 80 lks. dist., mkd. 1/4 S17 BT