

County Surveyor's Record, Douglas County, Oregon

14934

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

and bearing trees marked by Swearingen

A fir, 37 ins. diam., bears S. 52° E., 34 lks.
dist., with healed double blaze.

A sawed fir stump, 20 ins. diam., bears S. 49° W.,
38 lks. dist., with scribe marks BT visible on
opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the
ground, directly atop the iron rod, with brass cap mkd.

$$\begin{array}{r} T\ 31\ S\ R\ 8\ W \\ S\ 7\ |S\ 8 \\ \hline S\ 18\ |S\ 17 \\ 1973 \end{array}$$

from which new bearing trees

A fir, 26 ins. diam., bears N. 75° E., 77 lks.
dist., mkd. T31S R8W S8 BT.

A fir, 32 ins. diam., bears N. 2° W., 50 lks.
dist., mkd. T31S R8W S7 BT.

No other suitable bearing trees available within
limits.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, oak, madrone, chinquapin, cedar, and pin;
undergrowth, salal, huckleberry, salmonberry, live oak, hazel,
rhododendron, ferns, and vine maple.

From the 1/4 sec. cor. of secs. 7 and 8, monumented with an iron
post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground
with brass cap marked.

$$\begin{array}{r} \\ S\ 7\ |S\ 8 \\ \hline T\ 31\ S\ R\ 8\ W \\ 1962 \end{array}$$

from which the remaining original bearing tree

A cedar, 18 ins. diam., bears S. 65° E., 21 lks.
dist., with scribe marks 1/4 S visible on opened blaze.

and bearing trees marked by White, Corbin, and Beck

A fir, 14 ins. diam., bears S. 65° E., 42 lks.
dist., with healed blaze.

A fir, 32 ins. diam., bears N. 48° W., 34 lks.
dist., with scribe marks 1/4 S7 BT visible on
partially healed blaze.

and a bearing tree marked by John M. Powell, Deputy County
Surveyor, in 1967

A fir, 32 ins. diam., bears S. 60 1/2° W., 39 lks.
dist., with scribe amrkes 1/4 visible on partially
healed blaze.