

County Surveyor's Record, Douglas County, Oregon

14937

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, oak, madrone, chinquapin, cedar, and pine;
undergrowth, salal, huckleberry, salmonberry, live oak, hazel,
rhododendron, ferns, and vine maple.

From the cor. of secs. 5, 6, 7, and 8.

N. 4° 18' W. bet. secs. 5 and 6.

Descend 985 ft. over N. slope, through heavy timber and moderate undergrowth.

40.13 Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 31 S R 8 W
1/4
S 6 | S 5
1973

from which

A fir, 13 ins. diam., bears N. 89° E., 53 lks.
dist., mkd. 1/4 S5 BT.

A white fir, 12 ins. diam., bears S. 20° W.,
36 1/2 lks. dist., mkd. 1/4 S6 BT.

Descend 175 ft. over NE. slope.

51.00 Dice Creek, 5 lks. wide, course N. 55° W.; asc. 310 ft. over SW. slope.

68.25 Spur, slopes W.; desc. 195 ft. over N. slope.

75.85 The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

T 30 S R 8 W
S 31 | S 32
S 6 | S 5
T 31 S
1962

from which the remains of the original bearing trees

A fir snag, 63 ins. diam., bears S. 16° E.,
40 lks. dist., with fragmentary scribe marks
visible on bark blaze.

A fir snag, 12 ins. diam., bears N. 40° W., 8 lks.
dist., with no marks visible on rotted blaze.

and bearing trees marked by White, Corbin, and Beck

A white fir, 18 ins. diam., bears S. 42° E., 25 lks.
dist., with healed blaze.

A cedar, 8 ins diam., bears S. 89° W., 43 lks.
dist., with scribe marks T31S R8W S6 BT visible
on partially healed blaze.