

County Surveyor's Record, Douglas County, Oregon

14939

T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of township 24 south, range 6 west, Willamette Meridian, Oregon, in the portion covered by this resurvey is as follows:

The south and west boundaries and a portion of the subdivisional lines were surveyed by Robert Elder and Henry Gile, in 1853, as shown on the official plat of survey approved June 30, 1853. The survey of the subdivisional lines was completed by Williams R. Whipple, in 1891, as shown on the official plat of survey approved February 3, 1892. A portion of the west boundary of the township was retraced by Williams R. Whipple, in 1893, as shown on the official plat of survey of township 24 south, range 7 west, approved June 27, 1895. The east boundary of section 1, township 25 south, range 7 west, was surveyed by William P. Heydon, in 1897, as shown on the official plat of survey approved November 20, 1897.

Preliminary to the resurvey the lines of the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were re-established and remonumented at proportionate positions based on the original record. The re-tracement data were thoroughly verified and only the true line field notes are given herein. Only lines bounding, or crossing, public lands were blazed. All lines not forming a closure were measured twice.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated July 13, 1967.

The directions of lines were determined by solar instrument methods.

The geographic position of the corner of sections 5, 6, 31, and 32, on the south boundary of the township, as scaled from the Sutherlin Quadrangle Map, published by the United States Geological Survey, in 1954, is as follows:

Latitude 43° 26.0' N. Longitude 123° 26.7' W.

The mean magnetic declination is 19° 45' E.

Dependent Resurvey, Portion of S. Bdy., T. 24 S., R. 6 W.,
Willamette Meridian, Oregon
(Restoring the 1853 survey by Robert Elder and Henry Gile)

From the cor. of secs. 5, 6, 31, and 32, on the S. boundary of the Tp., perpetuated and recorded by the County Surveyor in 1962, monumented with an iron post, 1 in. diam., protruding 7 ins. above ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE

| | | |
|-------------|--|---|
| T 24 S | | |
| S 31 S 32 | | R |
| S 6 S 5 | | 6 |
| T 25 S | | W |
| 1962 | | |

from which the remaining original bearing trees

A root hole, bears N. 37° E., 64 lks. dist., with a rotted fir, 20 ins. diam., alongside, with scribe marks R6W T24S S32 BT visible on opened blaze. (Record, N. 32 1/2° E., 54 lks.)