

County Surveyor's Record, Douglas County, Oregon

14942

Dependent Resurvey, Portion of W. Bdy., T. 24 S., R. 6 W.

CHAINS

- 6.55 Bottom of descent, slopes W.; asc. 190 ft. over SW. slope.
- 13.30 Dirt road, 10 lks. wide, bears N. 60° W., and S. 60° E. curving to S.
- 27.90 Main ridge of Tye Mountain, bears NW. and SE.; desc. 120 ft. over broken NE. slope.
- 40.00 Point for the 1/4 sec. cor. of sec. 31 only, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- | | |
|-----|--------|
| | T 24 S |
| | S 31 |
| 1/4 | R 6 W |
| | 1967 |
- from which
- A fir, 8 ins. diam., bears N. 1 1/2° E., 217 lks. dist., mkd. 1/4 S31 BT.
- A fir, 6 ins. diam., bears S. 50 1/2° E. 22 lks. dist., mkd. 1/4 S31 BT.
- Descend 10 ft along E. slope.
- 40.94 Point for the 1/4 sec. cor. of sec. 36 only, on the E. bdy. of T. 24 S., R. 7 W.- at midpoint latitudinally.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- | | |
|--|----------|
| | T 24 S |
| | 1/4 S 36 |
| | R 7 W |
| | 1967 |
- from which
- A fir, 6 ins. diam., bears S. 23° W., 63 lks. dist., mkd. 1/4 S36 BT.
- A fir, 32 ins. diam., bears N. 69° W., 20 lks. dist., mkd. 1/4 S36 BT.
- The corner falls in head of ravine, drains E.
- Ascend 25 ft. along E. slope.
- 44.50 Spur, slopes NE.; desc. 670 ft. over steep N. slope changing to NE. slope.
- 61.10 Creek, 2 lks. wide, course N. 85° E.; asc. 520 ft. over steep broken SE. slope.
- 80.00 The cor. of secs. 30 and 31 only, determined at record bearing and distance from the original bearing trees:
- A burned fir, 39 ins. diam., bears N. 23° E., 37 lks. dist., with a healed blaze.
- A burned and sawed fir stump, 31 ins. diam., bears S. 3° E., 36 lks. dist., with scribe marks 4 S BT visible on opened blaze.