

# County Surveyor's Record, Douglas County, Oregon

14946

T. 25 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Dependent Resurvey, Portion of E. Bdy., T. 25 S., R. 7 W.,  
Willamette Meridian, Oregon

\*\*

From the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, determined at record bearing and distance from the original bearing trees:

A white Oak, 18 ins. diam., bears N. 68° E., 41 lks. dist., with scribe mark T visible on opened double blaze.

A root hole, bears S. 32° W., 88 lks. dist., with a rotted oak, size indeterminate, alongside, with no marks visible on rotted blaze.

and bearing trees mkd. by the County Surveyor in 1963

A black oak, 16 ins. diam., bears N. 41° E., 43 lks. dist., with scribe marks  $\frac{1}{4}$  S19 CS BT visible on open double blaze.

A white oak, 10 ins. diam., bears N. 32° W., 19 lks. dist., with scribe marks  $\frac{1}{4}$  S24 CS BT visible on open double blaze.

The corner point is now occupied by a white oak, 13 ins. diam., with a wire fence on W. side. I mark tree S19 on E. and  $\frac{1}{4}$  S24 on W. face.

from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 31° E., 3 lks dist., with brass cap mkd.  $\frac{1}{4}$  S19 RM 1968 and an arrow pointing to the corner.

N. 0° 06' W., bet. secs. 19 and 24, marking and blazing the true line.

Ascend 45 ft. over S. slope, through scattering timber and dense undergrowth, along wire fence.

- 4.00 Head of ravine, drains W.; asc. 70 ft. over SW. slope.
  - 9.00 Top of ascent, slopes SW.; desc. 10 ft. along W. slope.
  - 15.40 Spring seepage, drains S. 60° W.; asc. 330 ft. over S. slope changing to SW. slope, through logged area.
  - 22.80 The corner of wire fences extending N. 65° E., S., and W., bears East, 12 lks. dist.
  - 38.36 Point for the cor. of secs. 13, 18, 19, and 24, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

\*\*

(Restoring the 1853 survey by Elder and Gile, the 1877 survey by W. H. Byars, and the 1896 retracement and survey by W. P. Heydon)