

County Surveyor's Record, Douglas County, Oregon

1948

Dependent Resurvey, Portion of E. Bdy., T. 25 S., R. 7 W.

CHAINS

N. 0° 42' E., beginning new measurement.

Ascend 45 ft. over S. slope.

- 1.25 Spur, slopes N. 80° E.; desc. 200 ft. over N. slope.
- 5.50 Ravine, drains N. 70° E.; asc. 140 ft. over SE. slope.
- 10.60 Rocky spur, slopes E.; desc. 110 ft. over NE slope.
- 14.00 Ravine, drains S. 70° E.; asc. 200 ft. over SE. slope.
- 19.50 Spur, slopes N. 60° E.; desc. 300 ft. over NW. slope.
- 29.20 Top of rock bluff, 150 ft. high, bears E. and W.; desc. 485 ft. over bluff and N. slope.
- 39.90 The cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., determined at record distance from the remaining original bearing trees:

A sawed fir stump, 43 ins. diam., bears N. 78 3/4° E., 33 lks. dist., with no marks visible. (Record, N. 60° E.)

A shattered fir stump, 50 ins. diam., bears S. 5° E., 50 lks. dist., with bottom of original blaze visible. (Record, S. 28° E.)

A sawed fir stump, 64 ins. diam., bears N. 82° W., 50 lks. dist., with no marks visible. (Record, N. 68° W.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 25 S	
R 7 W	R 6 W
S 12	S 7
S 13	S 18

1968

from which new bearing trees

A fir, 15 ins. diam., bears N. 40° E., 127 lks. dist., mkd. T25S R6W S7 BT.

A fir, 6 ins. diam., bears S. 88° E., 55 1/2 lks. dist., mkd. T25S R6W S18 BT.

A fir, 6 ins. diam., bears S. 50 1/2° W., 38 lks. dist., mkd. T25S R7W S13 BT.

A fir, 5 ins. diam., bears N. 74° W., 64 1/2 lks. dist., mkd. T25S R7W S12 BT.

Land, mountainous.

Soil, rocky clay with rock outcropping.

Timber, fir, oak, maple, madrone, chinquapin, and alder; undergrowth, poison oak, fern, salal, hazel, vine maple, manzanita, arrowwood, blackberry, and young timber.