

County Surveyor's Record, Douglas County, Oregon

1950

Dependent Resurvey, Portion of N. Bdy., T. 25 S., R. 7 W.,

CHAINS

Dependent Resurvey, Portion of N. Bdy., T. 25 S., R. 7 W.,
Willamette Meridian, Oregon

(Restoring the 1893 survey by William R. Whipple,
and the 1896 retracement by William P. Heydon)

From the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., protruding 6 ins. above the ground, firmly set, with brass cap mkd. and witnessed as described in the official record of a 1958 dependent resurvey.

S. 89° 25' E., bet. secs. 2 and 35, marking and blazing the true line.

Ascend 15 ft. over NW. slope, through heavy young timber and dense undergrowth.

- 1.90 Spur, slopes N.; desc. 215 ft. over NE. slope.
- 8.30 Creek, 10 lks. wide, course N.; asc. 685 ft. over W. slope changing to broken NW. slope.
- 41.17 Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 7 W
¼ S 35
S 2
T 25 S
1967

from which

A fir, 10 ins. diam., bears N. 29½° W., 51½ lks. dist., mkd. ¼ S35 BT.

A fir, 8 ins. diam., bears S. 39¼° E., 78 lks. dist., mkd. ¼ S2 BT.

Ascend 35 ft. over W. slope.

- 44.70 Spur, slopes N. 25° W.; desc. 660 ft. over steep rocky NE. slope.
- 61.50 Creek, 7 lks. wide, course N. 15° W.; asc. 200 ft. over W. slope.
- 67.30 Rocky spur, slopes NW.; desc. 200 ft. over steep NE. slope.
- 71.00 Lost creek, 12 lks. wide, course N. 20° W.; asc. 100 ft. over W. slope changing to N. slope.
- 80.00 Creek, 7 lks. wide, course N. 70° W.; asc. 60 ft. over SW. slope.
- 82.17 Point for the cor. of secs. 1, 2, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.