

County Surveyor's Record, Douglas County, Oregon

1953

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1856-58 surveys by Dennis Hathorn,
the 1875 survey by William H. Byars, and the 1896
retracement by William P. Heydon)

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy.
of the Tp.

N. 86° 45' W., bet. secs. 13 and 24, marking and blazing
the true line.

Descend 10 ft. over SW. slope, through heavy young
timber and dense undergrowth, across partially logged area.

2.00 Creek, 2 lks. wide, course S.; asc. 80 ft. over E. slope.

3.60 Spur, slopes S. 20° E.; desc. 30 ft. over SW. slope.

5.00 Bottom of descent, slopes SE.; asc. 400 ft. over steep
rocky NE. slope.

15.25 Rocky spur, slopes SE.; desc. 20 ft. along S. slope.

20.00 Bottom of descent, slopes SE.; asc. 160 ft. over steep
rocky SE. slopes.

24.10 Rocky spur, slopes S.; desc. 300 ft. over W. slope
changing to steep NW. slope.

32.40 Spring seepage, drains SW.; asc. 75 ft. over steep SE. slope.

38.00 Top of ascent, slopes S.; desc. 20 ft. over SW. slope.

40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 13, and 24, restored by
the method of broken boundaries; there is no remaining
evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in
the ground, with brass cap mkd.

T 25 S R 7 W
 $\frac{1}{4}$ $\frac{S 13}{S 24}$
1968

from which

A fir, 53 ins. diam., bears N. 23° W., 70 lks.
dist., mkd. $\frac{1}{4}$ S13 BT.

An oak, 37 ins. diam., bears S. 37° W., 94 lks.
dist., mkd. $\frac{1}{4}$ S24 BT.

N. 86° 55' W., beginning new measurement.

Descend 165 ft. over gradual W. slope of benchland
changing to steep W. slope.

10.25 Spring seepage, drains S. 35° W.; desc. 300 ft. over
SW. slope.

19.60 Creek, 6 lks. wide, course S. 40° E.; asc. 700 ft. over
steep NE. slope.