

County Surveyor's Record, Douglas County, Oregon

2258

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

N. 1° 01' W., bet. secs. 33 and 34.

Ascend 35 ft. over SE. slope, through scattering timber and dense undergrowth, across partially logged area.

0.95 Wire fence, bears E. and W.

3.00 Spur, slopes E.; desc. 50 ft. over NE. slope.

12.65 Creek, 2 lks. wide, course E.; continue along E. slope.

13.50 Dry bed of creek, 2 lks. wide, course SE.; asc. 160 ft. over S. slope.

19.97 Point for the N 1/16 sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 33 | S 34
1968

from which

A fir, 35 ins. diam., bears N. 60° E., 89 lks. dist., mkd. N 1/16 S34 BT.

A cedar, 18 ins. diam., bears N. 27° W., 30½ lks. dist., mkd. N 1/16 S33 BT.

Ascend 70 ft. over SE. slope.

24.70 Spur, slopes S. 55° E.; desc. 50 ft. over NE. slope.

27.90 Dry bed of creek, 8 lks. wide, course S. 60° E.; asc. 385 ft. over SW. slope changing to S. slope.

36.10 Spur, slopes SE.; desc. 25 ft. along E. slope.

39.94 The cor. of secs. 27, 28, 33 and 34, determined at record distance from the original bearing trees:

A fir, 45 ins. dia., bears N. 84° E., 200 lks. dist., with no scribe marks visible on opened blaze.

A maple, 21 ins. diam., bears S. 36° E., 62 lks. dist., with no scribe marks visible on opened blaze. (Record, S. 40° E.)

A fir, 50 ins. diam., bears S. 1° W., 79 lks. dist., with no marks visible. (Record, S. 3° W.)

A madrone, 22 ins. diam., bears N. 21° W., 46 lks. dist., with no scribe marks visible on partially opened blaze. (Record, N. 20° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins in the ground, with brass cap mkd.

T 25 S R 7 W
S 28 | S 27
S 33 | S 34
1968

from which new bearing trees