

County Surveyor's Record, Douglas County, Oregon

1964

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

The corner falls on a spur, slopes W.

From this point, the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, bears N. $88^{\circ} 41'$ W., 40.50 chs. dist., determined at record bearing and distance from the original bearing trees:

An oak, 23 ins. diam., bears N. 45° E., 19 lks. dist., with scribe marks 16 visible in negative, on overgrowth of opened and rotted blaze.

A root hole, bears S. 48° E., 99 lks. dist., with an uprooted oak, 28 ins. diam., alongside, with no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 25 S R 7 W

FD OK PEE DOLA
DEC. 1968 M 107-38A&B

$\frac{1}{4}$ $\frac{S 16}{S 21}$

1968

from which new bearing trees

A fir, 12 ins. diam., bears N. 75° W., $27\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S16 BT.

An oak, 12 ins. diam., bears S. $24\frac{3}{4}^{\circ}$ E., $42\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S21 BT.

Land, mountainous except for river valley.

Soil, rocky clay with patches of loam in valley bottom. Timber, fir, oak, maple, madrone, cedar, alder, ash, myrtle, and cottonwood; undergrowth, young timber, fern, salal, poison oak, hazel, arrowwood; huckleberry, Oregon grape, vine maple, blackberry, and nettle.

From the cor. of secs. 14, 15, 22, and 23.

N. $89^{\circ} 51'$ W., bet. secs. 15 and 22.

Ascend 10 ft. along S. slope, through scattering timber and moderate undergrowth, across partially logged area.

1.00 Top of ascent, slopes S.; desc. 75 ft. along broken rocky S. slope.

9.00 Bottom of descent on rock outcropping, slopes S.; asc. 20 ft. along broken rocky S. slope.

18.30 Spur, ridge, bears NE. and SW.; desc. broken NW. slope.

28.50 Dirt road, 12 lks. wide, bears N. 70° E. and S. 70° W.

40.55 The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, determined at record bearing and distance from the remaining original bearing tree:

A white oak, 48 ins. diam., bears N. $72\frac{3}{4}^{\circ}$ W., 360 lks. dist., with scribe mark S visible on opened blaze.