

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

T 25 S R 7 W  
 $\frac{1}{4}$   
 S 16 | S 15  
 1968

*FD OK 1/92  
 G. BAUGHMAN  
 M112-43*

from which

A white fir, 11 ins. diam., bears N. 21° E., 27 lks. dist., mkd.  $\frac{1}{4}$  S15 BT.

A fir, 6 ins. diam., bears S. 52 3/4° W., 19 1/2 lks. dist., mkd.  $\frac{1}{4}$  S16 BT.

*FD OK PER LANG, 10/89, M109-3*

Descend 260 ft. over NW. slope.

45.50 Enter valley bottom, edge bears E. and W.; desc. 25 ft. over N. slope.

48.50 Asphalt surface road, 35 lks. wide, bears E. curving to NE. and W.

50.385 Point for the meander cor. of secs. 15 and 16 on right side of Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FD OK 12/77 BT  
 N. HIBBS M13A-1*

M C  


---

 S 16 | S 15  
 T 25 S R 7 W  
 1968

*FD OK 1/92  
 G. BAUGHMAN  
 M112-43*

from which

A white fir, 21 ins. diam., bears N. 63° E., 37 lks. dist., mkd. T25S R7W S15 MC BT.

A myrtle, 7 ins. diam., bears S. 64 1/2° W., 9 1/2 lks. dist., mkd. T25S R7W S16 MC BT.

*FD OK PER LANG, 10/89  
 M109-3*

Descend 15 ft. over N. slope.

51.70 Right bank of Umpqua River, bears E. curving to NE. and W. Continue across Umpqua River, course E. curving to NE.

60.60 Left bank of Umpqua River, bears NE. and W. and true point for the meander cor. of secs. 15 and 16 at proportionate distance; there is no remaining evidence of the original corner. It is impracticable to establish a permanent monument at this point.

Ascend 15 ft. over river bank.

61.59 Point for the witness cor. to the meander cor. of secs. 15 and 16 on the left bank of the Umpqua River.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 7 W  
S 16 | S 15  
 M C  
 W C  
 1968

from which