

County Surveyor's Record, Douglas County, Oregon

1968

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

From the cor. of secs. 27, 28, 33, and 34.

N. 85° 15' W., bet. secs. 28 and 33.

Ascend 250 ft. over E. slope, through medium timber and dense undergrowth, along S. edge of logged area.

4.00 Spur, slopes SE.; continue along S. slope.

8.00 Ravine, drains SE.; asc. 450 ft. over steep rocky SE. slope.

20.61 Point for the E 1/16 sec. cor. of secs. 28 and 33.

Set an iron post, 12 ins. long, 1 ins. diam., 4 ins. in drill hole, in solid rock, with brass cap mkd.

E 1/16 $\frac{S\ 28}{S\ 33}$
1968

from which

A cedar, 10 ins. diam., bears N. 6½° W., 67½ lks. dist., mkd. E 1/16 S28 BT.

A twin fir, 15 ins. diam., bears S. 17½° E., 57 lks. dist., mkd. E 1/16 S33 BT.

Ascend 30 ft. over SE. slope.

22.40 Ridge, bears NE. and SW.; desc. 290 ft. over NW. slope.

25.00 Dirt road, 15 lks. wide, bears NE. and SW. curving to S.

41.22 The ¼ sec. cor. of secs. 28 and 33, determined at record bearing and distance from the original bearing tree:

A cedar, 53 ins. diam., bears S. 85° W., 50 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 7 W
¼ $\frac{S\ 28}{S\ 33}$
1968

from which a new bearing tree

A fir, 13 ins. diam., bears N. 28° W., 31 lks. dist., mkd. ¼ S28 BT.

The corner falls at SW. corner of logged area.

N. 89° 50' W., beginning new measurement.

Descend 145 ft. along N. slope changing to NW. slope, through heavy timber and light undergrowth.

9.00 Bottom of descent, slopes NW.; asc. 10 ft. along N. slope.