

County Surveyor's Record, Douglas County, Oregon

12369

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS					
10.25	Spur, slopes NW.; desc. 55 ft. over NW. slope.				
13.45	Spring seepage, drains N. 10° W.; asc. 140 ft. over NE. slope.				
18.00	Spur, slopes N. 30° W.; desc. 360 ft. over NW. slope changing to W. slope.				
39.29	<p>The cor. of secs. 28, 29, 32, and 33, determined at record distance from the original bearing trees:</p> <p style="margin-left: 40px;">A cedar, 37 ins. diam., bears N. 11° E., 322 lks. dist., with scribe marks T25S R7W S28 BT visible on open blaze. (Record, N. 10° E.)</p> <p style="margin-left: 40px;">A fir, 43 ins. diam., bears S. 29½° W., 170 lks. dist., with a healed blaze. (Record, S. 29° W.)</p> <p style="margin-left: 40px;">A fir, 51 ins. diam., bears S. 83° W., 152 lks. dist., with a healed blaze. (Record, N. 86° W.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 25 S R 7 W</td></tr> <tr><td>S 29 S 28</td></tr> <tr><td>S 32 S 33</td></tr> <tr><td>1968</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 83½° E., 27 lks. dist., mkd. T25S R7W S33 BT.</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears N. 49° W., 41½ lks. dist., mkd. T25S R7W S29 BT.</p> <p>Land, mountainous. Soil, rocky clay with rock outcroppings. Timber, fir, hemlock, cedar, madrone, chinquapin, maple, and alder; undergrowth, young timber, vine maple, fern salal, hazel, arrowwood, poison oak, and Oregon grape.</p>	T 25 S R 7 W	S 29 S 28	S 32 S 33	1968
T 25 S R 7 W					
S 29 S 28					
S 32 S 33					
1968					
	<p>N. 0° 30' W., bet. secs. 28 and 29.</p> <p>Ascend 70 ft. along W. slope changing to SW. slope, through heavy timber and dense undergrowth.</p>				
5.50	Spur, slopes N. 75° W.; desc. 120 ft. over broken NW. slope.				
13.90	Spring seepage, drains N. 65° W.; asc. 10 ft. over SW. slope.				
15.00	Spur, slopes N. 65° W.; desc. 300 ft. over broken NW. slope. changing to N. slope.				
33.90	Creek, 1 lk. wide, course NW.; asc. 10 ft. along W. slope.				
39.36	Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.				