

County Surveyor's Record, Douglas County, Oregon

2970

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 25 S R 7 W
 $\frac{1}{4}$
 S 29|S 28
 1968

from which

A fir, 6 ins. diam., bears N. $68\frac{1}{2}^\circ$ E., 23 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

A fir, 7 ins. diam., bears N. 86° W., $31\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S29 BT.

The corner falls on a spur, slopes N. 70° W.

Descend 190 ft. over broken NW. slope.

59.04 Point for the N $1/16$ sec. cor. of secs. 28 and 29.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N $1/16$
 S 29|S 28
 1968

from which

A fir, 42 ins. diam., bears N. $55\frac{1}{2}^\circ$ E., $57\frac{1}{2}$ lks. dist., mkd. N $1/16$ S28 BT.

A cedar, 40 ins. diam., bears N. $26\frac{1}{2}^\circ$ W., 35 lks. dist., mkd. N $1/16$ S29 BT.

Descend 50 ft. over NW. slope changing to W. slope.

64.00 Spur, slopes N. 30° W.; desc. 300 ft. over NE. slope.

76.80 Spring seepage, drains N. 60° E.; desc. 35 ft. along E. slope changing to NE. slope.

78.72 The cor. of secs. 20, 21, 28, and 29, determined at record bearing and distance from the remaining original bearing trees:

A fir stump, 50 ins. diam., bears N. 47° E., 38 lks. dist., with no marks visible.

A fir stump, 60 ins. diam., bears S. 70° W., 25 lks. dist., with no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to solid rock, with brass cap mkd.

T 25 S R 7 W
 $\frac{S 20|S 21}{S 29|S 28}$
 1968

from which new bearing trees

A fir, 37 ins. diam., bears N. $66\frac{1}{2}^\circ$ E., 90 lks. dist., mkd. T25S R7W S21 BT.