

County Surveyor's Record, Douglas County, Oregon

1971

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS	
	<p>A fir, 13 ins. diam., bears S. 82 3/4° E., 56 1/2 lks. dist., mkd. T25S R7W S28 BT.</p> <p>A fir, 45 ins. diam., bears S. 4° W., 71 1/2 lks. dist., mkd. T25S R7W S29 BT.</p> <p>A fir, 8 ins. diam., bears N. 49 1/2° W., 35 lks. dist., mkd. T25S R7W S20 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, madrone, chinquapin, maple, and yew; undergrowth, young timber, fern salal, poison oak, vine maple, hazel, arrowwood, huckleberry, and Oregon grape.</p>
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 87° 14' W., bet. secs. 21 and 28/ Ascend 120 ft. over E. slope changing to S. slope, through heavy timber and dense undergrowth, along S. edge of logged area.</p>
8.40	Top of ascent, slopes S.; desc. 80 ft. over rocky SW. slope changing to W. slope.
12.00	Center of pond, 5 chs. diam., drains NW.; asc. 30 ft. over NE. slope changing to N. slope.
15.70	Creek, 1 lk. wide, course N. 30° E.; asc. 170 ft. over steep rocky NE. slope.
20.82	Point for the E 1/16 sec. cor. of secs. 21 and 28. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S } 21}{\text{S } 28} \\ 1968 \end{array}$
	from which
	<p>A fir, 45 ins. diam., bears N. 19° W., 44 1/2 lks. dist., mkd. E 1/16 S21 BT.</p> <p>A fir, 6 ins. diam., bears S. 70° E., 68 1/2 lks. dist., mkd. E 1/16 S28 BT.</p>
	Ascend 15 ft. along N. slope.
21.70	Spur, slopes N. 30° W.; desc. 100 ft. over NW. slope.
31.20	Spring seepage, drains NW.; desc. 100 ft. along N. slope changing to W. slope.
38.80	Dirt road, 15 lks. wide, bears NW. and SE.
41.64	The 1/4 sec. cor. of secs. 21 and 28, determined at record bearing and distance from the remaining original bearing tree:
	<p>A fir, 20 ins. diam., bears N. 38° W., 6 lks. dist., with scribe marks 4 S visible on opened blaze.</p>