

County Surveyor's Record, Douglas County, Oregon

1972

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 25 S R 7 W
 $\frac{1}{4}$ $\frac{S 21}{S 28}$
 1968

from which new bearing trees

A cedar, 10 ins. diam., bears N. 29½° W., 55 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

A fir, 32 ins. diam., bears S. 19½° E., 62 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

N. 89° 45' W., beginning new measurement.

Descend 10 ft. over W. slope.

0.70 Bottom of descent, slopes N. 55° W.; asc. 15 ft. along N. slope.

3.00 Spur, slopes NW.; desc. 185 ft. over W. slope.

14.50 Head of draw, drains S. 70° W.; desc. 90 ft. over SW. slope.

19.77 Point for the W 1/16 sec. cor. of secs. 21 and 28.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S 21}{S 28}$
 1968

from which

A fir, 33 ins. diam., bears N. 76° W., 57½ lks. dist., mkd. W 1/16 S21 BT.

A fir, 63 ins. diam., bears S. 50° W., 30 lks. dist., mkd. W 1/16 S28 BT.

Descend 65 ft. over SW. slope.

22.65 Dry bed of creek, 3 lks. wide, course N. 75° W.; asc. 5 ft. over NE. slope.

24.35 Spur, slopes N. 35° W.; desc. 335 ft. over W. slope.

37.70 Creek, 8 lks. wide, course N. 10° W.; asc. 60 ft. over steep E. slope.

39.54 The cor. of secs. 20, 21, 28, and 29.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, fir, hemlock, cedar, maple, madrone, yew, alder, and chinquapin; undergrowth, young timber, fern salal, vine maple, poson oak, Oregon grape, huckleberry, hazel, arrowwood, and salmonberry.

N. 0° 21' W., bet. secs. 20 and 21.