

# County Surveyor's Record, Douglas County, Oregon

2-573

Dependent Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS

Descend 95 ft. over steep NE. slope, through medium timber and dense undergrowth, across partially logged area.

- 5.80 Creek, 8 lks. wide, course N. 60° W. curving to NW. from S. 20° E.; asc. 130 ft. over SW. slope.
- 13.30 Spur, slopes SW.; desc. 65 ft. over NW. slope.
- 16.70 Spring seepage, drains W.; asc. 10 ft. over S. slope.
- 18.00 Spur, slopes W.; desc. 45 ft. over steep N. slope.
- 18.15 Dirt road, 15 lks. wide, bears E. and W.
- 19.61 Point for the S 1/16 sec. cor. of secs. 20 and 21.  
  
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  
  

S 1/16  
S 20|S 21  
1968

from which

  - A fir, 5 ins. diam., bears N. 88½° E., 31 lks. dist., mkd. S 1/16 S21 BT.
  - A fir, 7 ins. diam., bears S. 87½° W., 116 lks. dist., mkd. S 1/16 S20 BT.

Descend 105 ft. over steep N. slope.
- 21.40 Foot of steep descent and edge of valley bears E. and W.; desc. 10 ft. over valley bottom across open field.
- 23.65 Hubbard Creek, 30 lks. wide, course E.; asc. 20 ft. over SE slope.
- 27.50 Top of ascent, slopes E.; desc. 30 ft. over NW. slope changing to N. slope.
- 35.25 Hubbard Creek, 60 lks. wide, course N. 40° W. curving to N.; desc. 1 ft. along creek.
- 39.22 Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.  
  
Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.  
  

T 25 S R 7 W  
¼  
S 20|S 21  
1968

from which

  - A myrtle, 12 ins. diam., bears S. 15° E., 142 lks. dist., mkd. ¼ S21 BT.
  - A fir, 12 ins. diam., bears N. 21° W., 132 lks. dist., mkd. ¼ S20 BT.

The corner falls on left bank of Hubbard Creek, 40 lks. wide, course N. 30° E. curving to E., from S.

Ascend 50 ft. over SE. slope.