

County Surveyor's Record, Douglas County, Oregon

14978

T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 30 south, range 3 west, Willamette Meridian, Oregon.

The history of surveys in that portion of the township pertaining to this survey is as follows:

A portion of the subdivisional lines of the township was surveyed by Dennis Hathorn, in 1857.

The survey of the subdivisional lines was completed and a portion of the subdivisional lines was resurveyed or retraced by William M. Bushey, in 1893.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were re-established and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming closures were chained twice. Only those lines bounding or crossing public lands were blazed.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and Special Instructions, dated June 5, 1972, for group 776, Oregon.

The directions of the lines were determined by deflection angles from azimuths determined by direct solar observations.

The geographic position of the corner of sections 14, 15, 22, and 23, as scaled from the Days Creek, Oregon, quadrangle map, prepared by the United States Geological Survey, in 1954, is as follows:

Latitude $42^{\circ} 57.6' N.$ Longitude $123^{\circ} 02.4' W.$

The mean magnetic declination is $19^{\circ} 20' E.$

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 30 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by William M. Bushey,
Deputy Surveyor, in 1893)

From the corner of secs. 14, 15, 22, and 23, perpetuated and recorded by John H. Markham, Jr., Registered Logging Engineer, No. 2880, in 1960, monumented with an iron rod, $3/4$ in. diam., firmly set, extending 5 ins. above ground, from which the remains of the original bearing trees:

A burned fir stump, 30 ins. diam., bears
S. $10\ 1/2^{\circ} E.$, 30 lks. dist., no marks visible.

A decayed fir stump, size indeterminate, bears
S. $50^{\circ} W.$, 74 lks. dist., no marks visible.

A burned fir snag, 38 ins. diam., bears N. $45^{\circ} W.$,
29 lks. dist., no marks visible.