

# County Surveyor's Record, Douglas County, Oregon

14980

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

35.55

Ravine, drains S. 25° W.; asc. 15 ft. over SE. slope.

40.12

Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 3 W  
          S 15  
1/4               
          S 22  
          1972

from which

A fir, 7 ins. diam., bears N. 45° E., 72 1/2 lks. dist., mkd. 1/4 S15 BT.

A fir, 13 ins. diam., bears S. 60 1/4° W., 94 lks. dist., mkd. 1/4 S22 BT.

Corner is located on a spur, sloping S.

Descend 235 ft. over SW. slope.

47.35

Dirt road, 15 lks. wide, bears N. 30° W., and S. 30° E.

48.10

St. John Creek, 5 lks. wide, course S. 30° E., thence over broken creek bottom.

49.30

Creek, course N. 10° E.; continue over broken creek bottom.

49.90

Same creek, course S.; asc. 85 ft. over NE. slope.

55.00

Spur, slopes N.; desc. 10 ft. over NW. slope.

56.50

Creek, 3 lks. wide, course N. 30° E.; asc. 465 ft. over NE. slope.

72.95

Spur, slopes N. 30° E.; desc. 75 ft. over NW. slope.

76.00

Ravine, drains N.; asc. slightly over NE. slope.

80.24

The corner of secs. 15, 16, 21, and 22, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 75° E., 33 lks. dist., with the decayed remains of a fir alongside, size indeterminate, no marks visible.

A decayed fir stump, size indeterminate, bears S. 6 1/4° E., 45 lks. dist., with axe marks visible on old blaze.

A decayed fir stump, size indeterminate, bears S. 34° W., 42 1/2 lks. dist., no marks visible.

A root hole, bears N. 70 1/4° W., 10 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground and in a mound of stone, 2 ft. base, to top, with brass cap mkd.