

County Surveyor's Record, Douglas County, Oregon

14981

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

T 30 S R 3 W
S 16 | S 15

S 21 | S 22
1972

from which new bearing trees

A fir, 5 ins. diam., bears N. 55 1/2° E., 26 1/2 lks.
dist., mkd. X BT

A fir, 5 ins. diam., bears S. 41° E., 14 1/2 lks.
dist., mkd. X BT.

A fir, 6 ins. diam., bears S. 28° W., 1ks.
dist., mkd. T30S R3W S21 BT.

A fir, 5 ins. diam., bears N. 36 1/2° W., 48 lks.
dist., mkd. X BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, madrone, cedar, and oak; undergrowth, fern,
huckleberry, poison oak, and wild strawberry.

N. 0° 13' W., bet. secs 15 and 16.

Descend 300 ft. over NW. slope, through heavy reproduc-
tion and moderate undergrowth.

8.05 Creek, 4 lks. wide, course N. 70° E.; asc. 315 ft. over
SE. slope.

13.20 Spring, flows S. 30° E.

18.00 Spur, slopes S. 65° E.; desc. 25 ft. over NE. slope.

19.05 Ravine, drains E.; asc. 35 ft. over SE. slope

23.40 Spur, slopes S. 75° E.; desc. 390 ft. over NE. slope.

36.75 Creek, 5 lks. wide, course N. 65° E.; asc. 55 ft. over
SE. slope.

38.45 Dirt road, 15 lks. wide, bears N. 80° E., and S. 60° W.

39.98 The 1/4 sec. cor. of secs. 15 and 16, determined at
record bearing and distance from the remaining original
bearing tree:

A cedar, 18 ins. diam., bears N. 39 1/2° W., 34 lks.
dist., with scribe marks S BT visible on opened
Blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 30 S R 3 W
1/4
S 16 | S 15
1972

from which new bearing trees

A fir, 9 ins. diam., bears N. 50 1/4° E., 39 lks.
dist., mkd. 1/4 S15 BT.