

County Surveyor's Record, Douglas County, Oregon

14882

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A fir, 6 ins. diam., bears N. 21 1/2° W., 27 1/2 lks. dist., mkd. 1/4 S16 BT.

N. 0° 25' W., beginning new measurement.

Ascend 190 ft. over SE. slope.

8.05 Spur, slopes S. 70° E., desc. 45 ft. over NE slope.

11.80 Ravine, drains S. 70° E.; asc. 320 ft. over SE. slope.

20.50 Spur, slopes S. 60° E.; desc. 230 ft. over broken NE. slope.

34.55 Ravine, drains E.; asc. 185 ft. over SE. slope.

40.37 The corner of secs. 9, 10, 15, and 16, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/2 ins. diam., firmly set, extending 10 ins. above ground, with top mkd.

| | |
|--------|--------|
| T 30 S | |
| S 9 | S 10 R |
| S 16 | S 15 3 |
| | 1963 W |

from which the remaining original bearing trees

A fir, 25 ins. diam., bears N. 60° E., 14 1/2 lks. dist., with healed blaze. Re-marked by Byron, in 1963, with scribe marks CS visible on pitched over blaze.

A madrone, 8 ins. diam., bears S. 10 1/2° E., 33 lks. dist., no marks visible on opened and burned blaze.

A fir, 14 ins. diam., bears S. 20 1/2° W., 76 lks. dist., with fragmentary scribe marks visible on opened and burned blaze.

and bearing trees marked by Byron in 1963

A fir, 22 ins. diam., bears S. 11° W., 78 lks. dist., with fragmentary scribe marks visible on pitched over blaze.

A fir, 36 ins. diam., bears North, 8 1/2 lks. dist., with fragmentary scribe marks visible on pitched over blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, madrone, cedar, oak, and maple; undergrowth, huckleberry, Oregon grape, fern, poison oak, and blackberry.

From the corner of secs. 15, 16, 21, and 22.

S. 89° 41' W., bet. secs. 16 and 21.

Descend 105 ft. over NW. slope, through heavy reproduction and moderate undergrowth.

6.05 Ravine, drains N. 30° W., asc. 15 ft. over NE. slope.