

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
7.20	Spur, slopes N.; desc. 60 ft. over NW. slope.
8.90	Creek, 3 lks. wide, course N. 40° E.; asc. 165 ft. over SE. slope
16.65	Spur, slopes S.; desc. 20 ft. over SW. slope.
18.95	Same creek, course S. 35° E.; asc. 100 ft over NE. slope.
20.95	Creek, 2 lks. wide, course S.; continue desc. 545 ft. over NE. slope.
39.45	Enter scattering timber.
40.10	Dirt road, 20 lks. wide, bears N. 65° W., and S. 75° E.
40.22	Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 30 S R 3 W 1/4 $\frac{S 16}{S 21}$ 1972</p>
	from which
	A fir, 14 ins. diam., bears N. 33 1/2° W., 88 lks. dist., mkd. 1/4 S16 BT.
	A fir, 13 ins. diam., bears S. 54° W., 93 lks. dist., mkd. 1/4 S21 BT.
	Corner is located on a spur sloping S. 45° E.
	Descend 180 ft. over SW. slope.
56.25	Ravine, drains S. 20° W.; asc. 55 ft. over SE. slope.
61.10	Spur, slopes S. 10° E.; desc. 110 ft. over SW. slope.
71.10	Ravine, drains S. 20° E.; asc. 170 ft. over SE. slope.
80.44	The corner of secs. 16, 17, 20, and 21, perpetuated and recorded by John H. Markham, Jr., Registered Logging Engineere, No. 2880, in 1952, monumeted with an iron pipe, 1 in. diam., firmly set, extending 6 ins. above ground, from which the remains of the original bearing trees:
	A fir, 35 ins. diam., bears S. 23 1/2° E., 53 lks. dist., with fragmentary scribe marks visible on opened blaze, and additional scribe marks S 21, added by Markham, visible on bark.
	A root hole, bears S. 30 1/2° W., 71 1/2 lks. dist.
	and bearing trees marked by Markham
	A madrone, 23 ins. diam., bears N. 66° E., 80 lks. dist., with scribe marks S16 288 T30S R3W visible on bark.
	A maple, 20 ins. diam., bears S. 49° W., 65 lks. dist., with healed blaze.