

# County Surveyor's Record, Douglas County, Oregon

14987

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 27 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

T 27 S R 4 W  
S C  
S 33 | S 34  
S 4 | S 3  
T 28 S  
1958

from which trees mkd. by Zirpel and Glenn

A cedar, 16 ins. diam., bears N. 48° E., 119 lks. dist., with healed blaze.

A cedar, 17 ins. diam., bears S. 23° E., 110 lks. dist., with healed blaze.

A fir, 16 ins. diam., bears N. 12 3/4° W., 110 lks. dist., with healed blaze

and a new bearing tree

A fir, 10 ins. diam., bears S. 58° W., 120 lks. dist., mkd. T28S R4W S4 SC BT.

N. 0° 06' E., bet. secs. 33 and 34, marking and blazing the true line.

Ascend 70 ft. over SW. slope, through scattering timber and light undergrowth.

3.25 Spur, slopes S. 75° W.; desc. 15 ft. over NW. slope.

7.45 Ravine, drains S. 80° W.; asc. 25 ft. over general W. slope.

23.50 Ridge, bears N. 15° W. and S. 15° E.; desc. 335 ft. over NE slope.

35.30 Ravine, drains N. 20° E.; asc. 35 ft. over SE. slope.

40.19 Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 27 S R 4 W  
1/4  
S 33 | S 34  
1974

from which

A fir, 13 ins. diam., bears N. 40 1/2° E., 32 lks. dist., mkd. 1/4 S34 BT.

A fir, 16 ins. diam., bears N. 55° W., 31 1/2 lks. dist., mkd. 1/4 S33 BT

Ascend 10 ft. over SE. slope, along E. edge of timber line.

45.15 Spur ridge, bears E. and W.; desc. 260 ft. over NE. slope.

60.285 Point for the N 1/16 sec. cor. of secs. 33 and 34.