

County Surveyor's Record, Douglas County, Oregon

14988

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 4 W., Willamette Meridian, Oregon.

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

N 1/16
S 33 | S 34
1974

from which

A cedar, 22 ins. diam., bears S. 37° E., 35 lks. dist., mkd. N 1/16 S34 BT.

A cedar, 9 ins. diam., bears N. 2 1/2° W., 21 1/2 lks. dist., mkd. N 1/16 S33 BT.

Descend 300 ft. over broken NE. slope.

80.38 The cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by the County Surveyor, in 1959, further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, and redescribed by James E. Jelley, in 1970, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
S 28 | S 27
S 33 | S 34
T 27 S R 4 W
1959

from which the remains of the original bearing tree

A cedar snag, 20 ins. diam., bears N. 84° E., 18 lks. dist., no marks visible on opened blaze.

and trees mkd. by the County Surveyor, in 1959

A root hole, bears S. 88 1/2° E., 105 lks. dist., with a down fir alongside, 12 ins. diam., with scribe marks BT visible on open lower blaze and healed upper blaze.

A cedar, 17 ins. diam., bears S. 13° E., 51 lks. dist., with scribe marks T27S R4W S34 CS visible on open double blaze.

A cedar, 16 ins. diam., bears S. 51° W., 13 lks. dist., with fragmentary scribe marks visible on open double blaze.

A yew, 15 ins. diam., bears N. 44 1/2° W., 28 lks. dist., with scribe marks T27S R4W S28 CS visible on open double blaze

and a tree mkd. by Godfrey

A yew, 6 ins. diam., bears N. 11° E., 35 lks. dist., with scribe marks S27 CS BT visible on open double blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, madrone, alder, maple, hemlock, and oak; undergrowth, poison oak, salal, Oregon grape, arrow-wood, ceanthus, fern, and hazel.