

County Surveyor's Record, Douglas County, Oregon

14991

T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of a dependent resurvey of a portion of the south boundary, township 21 south, range 6 west, Willamette Meridian, Oregon.

The history of surveys of that portion of township 21 south, range 6 west, Willamette Meridian, Oregon, included in the following resurvey, is as follows:

The south boundary of township 21 south, range 6 west, and a portion of the subdivisional lines of township 22 south, range 6 west, were surveyed by Harvey Gordon and Charles T. Gardner in 1855-56.

The west four miles of the south boundary were resurveyed and a portion of the subdivisional lines was surveyed by William P. Wright, in 1884.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were re-established and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines were chained twice to preclude error.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and the special Instructions dated September 25, 1973, under Group Number 828, Oregon.

The directions of the lines were determined by the solar compass method and by azimuths obtained from direct solar observations.

The geographic position of the southeast corner of section 33, as scaled from the Drain, Oregon, quadrangle map, prepared by the United States Geological Survey, in 1954, is as follows:

Latitude 43° 41.6' N. Longitude 123° 24.5' W.

The mean magnetic declination is 19° 30' E.

Dependent Resurvey of a Portion of the South Boundary
T. 22 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the 1855-56 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, and the 1884 resurvey by William P. Wright, Deputy Surveyor)

Beginning at the cor of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1961, from original evidence no longer in existence, monumented with an iron post, 1 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 21 S
R 6 W
S 33 | S 34
S 4 | S 3
T 22 S
1961