

County Surveyor's Record, Douglas County, Oregon

14992

Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which bearing trees mkd. by Godfrey

A fir snag, 14 ins. diam., bears N. 17° E., 16 lks. dist., with healed double blaze.

A yew, 10 ins. diam., bears N. 48° W., 75 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

A white fir snag, 26 ins. diam., bears S. 3° W., 57 lks. dist., with healed double blaze.

A white fir, 15 ins diam., bears S. 72° W., 46 lks. dist., with healed double blaze.

and a bearing tree mkd. by the County Surveyor, in 1973

A maple, 8 ins. diam., bears S. 48° E., 16 lks. dist., with scribe marks S3 CS BT visible on bark.

No other suitable bearing tree available within limits.

The corner is located 2 lks. S. of intersection of fences, extending S. and W.

S. 89° 48' W., bet. secs. 4 and 33, marking and blazing the true line.

Descend 390 ft. over W. slope, through scattered timber and light undergrowth, along barbed wire fence.

18.20 Barbed wire fence, bears S. and E.

19.70 Parker Creek, 4 lks. wide, course S. 10° W.; asc. 230 ft. over SE. slope; also enter moderate timber, edge bears generally N. and S.

25.11 Spur, slopes S. 10° E.; desc. 60 ft. over SW. slope.

26.91 Creek, 1 lk. wide, course S. 12° W.; asc. 160 ft. over SE. slope.

35.38 Top of ascent, slopes S.; desc. 30 ft. over SW. slope.

39.53 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 21 S R 6 W

1/4 S 33

S 4

1973

from which

A fir, 10 ins. diam., bears N. 29° W., 45 lks. dist., mkd. 1/4 S33 BT.

A cedar, 10 ins. diam., bears S. 70° E., 16 1/4 lks. dist., mkd. 1/4 S4 BT.

Descend 30 ft. over SW. slope